



Epson Certified Label Program

Labels specifically designed and manufactured to get the most out of your EPSON Label printer



Quality Guaranteed

- ▶ All materials are tested and approved to work with EPSON label printers
- ▶ All materials are EPSON approved
- ▶ Materials are never substituted

Performance Guaranteed

- ▶ 100% satisfaction guarantee
- ▶ All materials are specifically approved to maximize EPSON printer performance

ISO 9001: 2015 Manufacturing Facility

- ▶ Raw materials are subject to rigorous quality inspection and QC process
- ▶ Finished products go through quality production inspection process along with final product configuration and packaging QC process

Benefits of EPSON Certified Labels

- Hundreds of Labels with Quick Delivery
- Guaranteed Performance = Piece of Mind
- Reliable and Superior Print Quality
- Maximize Printer Performance
- Consistent Printer UP Time
- Best in class adhesion and application performance
- Excellent Customer Service and Technical Support



With  , every label-in every run-will...

- ✓ Print properly
- ✓ Adhere securely
- ✓ Look ideal
- ✓ Perform proper



Epson Certified Label Program

Material Selector Guide

- RL-11 Certified Premium Matte Paper
- RL-25 Certified Premium High Gloss Paper
- RL-35 Certified Craft Paper - Smooth
- RL-55 Certified Premium Matte Poly (GHS Approved)
- RL-57 Certified Extreme Matte Poly (GHS Approved)
- RL-60 Certified Gloss Poly
- RL-67 Certified Satin Poly

Material	Material Description	Adhesive type	Applications	Min. Application Temp	Service Temp Range	Relative Cost
RL-11	Premium Matte Paper	Permanent Acrylic	Packaging, Distribution	-20°	-65°F to +200°F	\$
RL-25	Premium High Gloss Paper	Permanent Acrylic	Product, Packaging, Prime	-20°	-65°F to +200°F	\$\$
RL-35	Craft Paper - Smooth	Permanent Acrylic	Product, High Image	25°	-10°F to 200°F	\$\$\$\$
RL-55	Premium Matte Polypropylene	Permanent Acrylic	GHS, Chemical, Medical, Pharma	25°	-10°F to 200°F	\$\$\$
RL-57	Extreme Matte Polypropylene	Permanent Acrylic	GHS, Chemical, Medical, Pharma	20°	-20°F to 300°F	\$\$\$\$\$
RL-60	Gloss Polypropylene	Permanent Acrylic	Prime, Product	-20°	-65°F to +200°F	\$\$\$\$
RL-67	Satin Polyolefin	Permanent Acrylic	Medical, Pharma, Product	-20°	-65°F to +200°F	\$\$\$\$

Surface to be Labeled	Surface to be Labeled															
	Corrugate	Paper	Packaging Films	Most Plastic Films	Metals	Rough Surfaces	Curved Surfaces	Moist Surfaces	Environment	Outdoor	Indoor	Resistance	Moisture	Oil & grease	Alcohol	Abrasion
RL-11	Green	Green	Red	Red	Green	Yellow	Red	Red	White	Yellow	Green	White	Yellow	Red	Red	Yellow
RL-25	Green	Green	Green	Green	Green	Green	Yellow	White	White	Yellow	Green	White	Yellow	Yellow	Red	Yellow
RL-35	Green	Green	Green	Green	Green	Yellow	Yellow	White	White	Yellow	Green	White	Yellow	Yellow	Yellow	Green
RL-55	Green	Green	Green	Green	Yellow	Yellow	Green	White	White	Green	Green	White	Green	Green	Green	Green
RL-57	Green	Green	Green	Green	Green	Yellow	Green	White	White	Green	Green	White	+	+	+	+
RL-60	Green	Green	Green	Green	Green	Yellow	Green	White	Red	Green	White	Yellow	Yellow	Red	Red	Yellow
RL-67	Green	Green	Green	Green	Green	Green	Green	White	Green	Green	White	Green	Yellow	Red	Yellow	Yellow



Epson Certified Label Program

Available with perf between labels upon request
 2 rolls per case
 1/8 gap between each label with 1/8 corner radius
 All labels are Certified for the EPSON C6500 Printer

Label Width	Label Length	Labels Across	# of Labels per Roll	Rolls per Case	Labels per Case
1	1	1	2450	2	4900
1	1.5	1	1720	2	3440
1.5	1	1	2450	2	4900
2	1	1	2450	2	4900
2	2	1	1315	2	2630
2	6	1	450	2	900
2.5	1.5	1	1720	2	3440
3	1	1	2450	2	4900
3	2	1	1315	2	2630
3	3	1	895	2	1790
3	4	1	675	2	1350
3	5	1	545	2	1090
3.5	8	1	350	2	700
4	1	1	2450	2	4900
4	2	1	1315	2	2630
4	3	1	895	2	1790
4	4	1	675	2	1350
4	5	1	545	2	1090
4	6	1	455	2	910
4	8	1	340	2	680
6	4	1	675	2	1350
7	10	1	275	2	550
8	6	1	455	2	910
8	10.875	1	250	2	500
8	13.875	1	200	2	400



With  , every label-in every run-will...

- ✓ Print properly
- ✓ Adhere securely
- ✓ Look ideal
- ✓ Perform proper